Distributed by Conrad Electronic SE • Klaus-Conrad-Str. 1 • D-92240 Hirschau

Datasheet

Item no. 701308/ 701309/ 701310/ 701316/ 701318/ 701319/ 701311/ 701312 / 701313/ 701320/ 701321/ 701322/ 702182/ 702211/ 702165/ 702477/ 702462/ 702197

V1_0717_01_en


TECHNICAL DESCRIPTION

Lamp Ratings


Lamp Type	LED		
Rated Voltage	AC/DC6V	AC/DC12V	AC/DC24V
	AC/DC110V	AC/DC220V	
Colours	R G Y O B W		
Life	About 40,000 hours		

Note: There are protective resistor in the lamp, special voltage rate can be made to order.

Switching Operation



NO.2



NO.3

Soldering information

- Handiwork solding: Soldering iron 30W or under at 230℃ for 3 sec max.

Datasheet

Item no. 701308/ 701309/ 701310/ 701316/ 701318/ 701319/ 701311/ 701312 / 701313/ 701320/ 701321/ 701322/ 702182/ 702211/ 702165/ 702477/ 702462/ 702197


V1_0717_01_en

METAL PUSHBUTTONS

RING ILLUMINATED PUSHBUTTON



- Φ19mm diameter
- 5A, 250VAC
- 1NO1NC/2NO2NC
- The Front Shape：Flat Round
- The crust material：Stainless Steel
- Ring Illuminated
- IP Degree：IP67



701308 : Push Button Switch, Ring, Momentary, 1NO1NC, 12V, Red

701309 : Push Button Switch, Ring, Momentary, 1NO1NC, 12V, Green

701310 : Push Button Switch, Ring, Momentary, 1NO1NC, 12V, Blue

701316 : Push Button Switch, Ring, Alternate, 1NO1NC, 12V, Red

701318 : Push Button Switch, Ring, Alternate, 1NO1NC, 12V, Green

701319 : Push Button Switch, Ring, Alternate, 1NO1NC, 12V, Blue

701311 : Push Button Switch, Ring, Momentary, 2NO2NC, 12V, Red

701312 : Push Button Switch, Ring, Momentary, 2NO2NC, 12V, Green

701313 : Push Button Switch, Ring, Momentary, 2NO2NC, 12V, Blue

701320 : Push Button Switch, Ring, Alternate, 2NO2NC, 12V, Red

701321 : Push Button Switch, Ring, Alternate, 2NO2NC, 12V, Green

701322 : Push Button Switch, Ring, Alternate, 2NO2NC, 12V, Blue

702182 : Push button switch in black, dia.19mm, Ring illuminated, LED Blue

702211 : Push button switch in black, dia.19mm, Ring illuminated, LED Green

702165 : Push button switch in black, dia.19mm, Ring illuminated, LED Red

702477 : Push button switch in black, dia.19mm, Ring illuminated, LED Red & Green

702462 : Push button switch in dual, dia.19mm, Ring illuminated, LED Red & Green

702197 : Push button switch in black, dia.19mm, Ring illuminated, LED White

Datasheet

Item no. 701308/ 701309/ 701310/ 701316/ 701318/ 701319/ 701311/ 701312 / 701313/ 701320/ 701321/ 701322/ 702182/ 702211/ 702165/ 702477/ 702462/ 702197

METAL PUSHBUTTONS

		701308 701309 701310 701316 701318 701319 701311 701312 701313 701320 701321 701322 702182 702211 702165 702477 702462 702197
Specification		
The Front Shape		Flat Round
Terminations		Soldering(Pin Terminal)/2.8mm tabs
Switching		NO.3
Max. Switch Rating		5A/250VAC
Contact Resistance		≤50mΩ
Insulation Resistance		≥1000MΩ
Dielectric Strength		2000VAC
Operating Temp.		- 20℃ ~ + 70℃
Mechanical life		1,000,000 cycles
Electrical life		50,000 cycles
Contact material		Silver Alloy
Panel Thickness		1~10mm
Torque		5~14Nm
Operation Pressure		5.5N
IP Degree		IP67
Material	Button	Stainless Steel
	Body	Stainless Steel
	Base	PBT
	RoHS	Yes
LED Spec.	Type	Ring Illuminated(LED)
	Rated Voltage	6V / 12V / 24V / 110V / 220V
	Color	R G Y O B W
	Life	40,000 hours

This is a publication by Conrad Electronic SE, Klaus-Conrad-Str. 1, D-92240 Hirschau (www.conrad.com).
All rights including translation reserved. Reproduction by any method, e.g. photocopy, microfilming, or the capture in electronic data processing systems require the prior written approval by the editor. Reprinting, also in part, is prohibited. This publication represents the technical status at the time of printing.

© Copyright 2017 by Conrad Electronic SE.