

PDHxx-5,08





Male plug-in connector - Horizontal - Dual row - Pitch 5,08mm - 02÷12 poles

GENERAL INFORMATION	
pitch:	5,08 mm
housing height:	28,82 mm
housing depth:	22.3 mm
dimensional class:	medium
wire section:	-
clamp opening size:	
wire stripping:	-
operating temperature:	-40°C ÷ +130°C

ELECTRICAL CHARACTERISTICS	
current:	10A
voltage:	500V
impulse voltage:	6 kV

MECHANICAL CHARACTERISTICS		
-		-

APPROVALS DATA

	EN 61984	EN 61984	UL 1059
current:	12A	12A	12A factory / 12A field
voltage:	250V	250V	300V
FILE:	CA02.04178	40005779	E178356

Copyright ©2020 - euroclamp - http://www.euroclamp.it

MATERIALS

housing:	PA - UL 94 V0
screw:	n/a
clamp/spring:	n/a
terminal:	Tin-plated copper alloy

AVAILABLE COLOURS

GN (STD) GY BK BL RD YL OG

other colours: upon request

poles	P/N	pcs/pack	W [Kg]*	W [Kg]*
02	PDH02-5,08	N/A	N/A	N/A
03	PDH03-5,08	N/A	N/A	N/A
04	PDH04-5,08	N/A	N/A	N/A
05	PDH05-5,08	N/A	N/A	N/A
06	PDH06-5,08	N/A	N/A	N/A
07	PDH07-5,08	N/A	N/A	N/A
08	PDH08-5,08	N/A	N/A	N/A
09	PDH09-5,08	N/A	N/A	N/A
10	PDH10-5,08	N/A	N/A	N/A
11	PDH11-5,08	N/A	N/A	N/A
12	PDH12-5,08	N/A	N/A	N/A

Copyright ©2020 - euroclamp - http://www.euroclamp.it