
385102400060

Relay interface module (EMR or SSR) 0.1 - 2 - 3 - 5 - 6 - 8 - 16 A



This image is for illustrative purposes only and therefore may not represent the exact product code. Colours may vary.

Technical description:
Relay interface modules, Electromechanical relay, with screw terminal, 1 pole, CO (nPDT), 6 A, AgNi, DC coil, 220 V, operating from 176 to 264 V, rated power 0.9 W, consumption 4 mA, holding voltage 144 V, must drop-out voltage 12 V, option: AC or AC/DC, ambient temperature from -40 to +55 °C

BROWSE PRODUCT PAGE

Technical Features:

Ambient temperature range:	-40...55 °C
Commercial Description:	Relay Interface Module with single output, width 6,2 mm. Equipped with screw terminals. With AC or DC output circuit and DC input circuit. 35 mm rail (EN 60715) mounting. Designed for interfacing with PLC systems.
Contact configuration:	1 pole, CO (nPDT)
Dimensions:	6.2x88.4x72.1 mm
Electrical life:	60000 cycles
Insulation coil/contacts:	6 kV
Nominal voltage DC:	220 V
Operating range DC:	176...264 V
Rated contact voltage:	250 V AC
Rated current (contacts):	6
Rated power DC:	0.9 W
Supply:	DC coil
Certifications and quality approvals (according to type):	

The information, technical details, data and features contained in this document are subject to change or modification at any time.
It is for information purposes only and does not form
the basis of a contract.

Need more information?
Contact our sales Find a dealer

Finder 2025 - All rights reserved
Findernet.com
Technical Information