
393102400060

Relay interface module (EMR or SSR) 0.1 - 2 - 6 A



This image is for illustrative purposes only and therefore may not represent the exact product code. Colours may vary.

Technical description:
MasterPLUS - EMR - Relay interface modules, Screw terminal, fuse-protectable output, 1 pole, CO (nPDT), 6 A, AgNi, AC/DC coil, 240 V, operating from 20.4 to 264 V (AC)/(DC), rated power 1.5 VA (AC) / 0.3 W (DC), consumption 19 mA, holding voltage 144 V (AC)/(DC), must drop-out voltage 2.4 V (AC)/(DC), ambient temperature from -40 to +70 °C

BROWSE PRODUCT PAGE

Technical Features:

Ambient temperature range:	-40...70 °C
Commercial Description:	MasterPLUS EMR relay interface module with screw terminals, 1 CO – 6 A. Accepts fuse holder module allowing for protection of the output circuit – saving space. Width 6.2mm.
Contact configuration:	1 pole, CO (nPDT)
Dimensions:	6.2x94.3x87.2 mm
Electrical life:	60000 cycles
Insulation coil/contacts:	6 kV
Nominal voltage AC:	240 V
Nominal voltage DC:	240 V
Operating range AC:	20.4...264 V
Operating range DC:	20.4...264 V
Rated contact voltage:	250 V AC
Rated current (contacts):	6
Rated power AC:	1.5 VA
Rated power DC:	0.3 W
Supply:	AC/DC coil
Certifications and quality approvals (according to type):	

The information, technical details, data and features contained in this document are subject to change or modification at any time.
It is for information purposes only and does not form
the basis of a contract.

Need more information?
Contact our sales Find a dealer

Finder 2025 - All rights reserved
Findernet.com
Technical Information