Data sheet Product SLV W 7 117 40 Z



PCB connectors>Male headers


two rows, □ 0.4 mm; pitch 1.27 x 1.27 mm

- for interconnections of stacked PCBs
- within the total length of the pin the insulator position can be changed as required
- **separable!** any requested number of contact can be delivered

Features

pitch:	**1.27 x 1.27 mm**
no. of contacts:	**40**
contact material:	**CuZn-alloy**
surface of contact:	**tin-plated**
surface contact / contact sleeve:	• **Ni+≥0.2µm Au** • **Ni+4...6µm Sn**
version:	**sandwich**
volume resistance:	**≤5 mΩ**
nominal current:	**1.5 A**
nominal voltage:	**125 V AC**
test voltage:	**300 V**
insulating body material:	**PA 4.6. GF**
temperature range:	• **-40°C... +163°C** • **(260°C/10 s)**
class of inflammability:	**UL 94 V-0**
specific insulation resistance:	**$>10^7$ Ω·m**
connection type:	**THT (Einlöt)**
reflow solderable:	**yes**

Technical Drawing



A:	11.7 mm
L:	17.2 mm

Fischer Elektronik GmbH & Co. KG
DEUTSCHLAND • GERMANY • ALLEMAGNE
Nottebohmstraße 28
58511 Lüdenscheid
Telefon +49 2351 435-0
Telefax +49 2351 45754
info@fischerelektronik.de
www.fischerelektronik.de