Silicone cables with extended temperature range
Flexibility simplifies installation where space is limited
Possesses insulating properties after combustion due to remaining SiO2 ash on the conductor



CE RoHS

Halogen-free

Cold-resistant

Temperature-resistant

Info
The classic for multi-functional use

Application range
Areas with high ambient temperatures where insulating and sheath materials of conventional cables will embrittle after a short while
Typical fields of application- Steel, ceramic and iron works- Bakery equipment and industrial furnaces- Electric motor industry- Sauna/solarium construction- Thermal and heating elements- Lighting technology- Ventilator engineering- Air-conditioning technology- Galvanisation technology

Design
Fine-wire, tinned-copper conductor
Silicone-based core insulation
Cores twisted in layers
Silicone-based outer sheath,colour red-brown

Product features
Halogen-free and flame-retardant (IEC 60332-1-2)
Resistant to a multitude of oils, alcohols, vegetable and animal fats and chemical substances

Remark
Unless specified otherwise, the shown product values are nominal values. Detailed values (e.g. tolerances) are available upon request.
Copper price basis: EUR 150/100kg. Refer to catalogue appendix T17 for the definition and calculation of copper-related surcharges.
Please find our standard lengths at: www.lappkabel.de/en/cable-standardlengths
Packaging size: coil ≤ 30 kg or ≤ 250 m, otherwise drum
Please specify the preferred type of packaging (e.g. 1 x 500 m drum or 5 x 100 m coils).
Photographs are not to scale and do not represent detailed images of the respective products.

PN 0486/01_03.10 ©2012 Lapp Group - Technical changes reserved
Photographs are not to scale and do not represent detailed images of the respective products.

Technical Data

Core identification code:	Colours according to VDE 0293-308, refer to Appendix T9 From 6 cores: black with white numbers
Classification:	ETIM 5.0 Class-ID: EC001578 ETIM 5.0 Class-Description: Flexible cable
Specific insulation resistance:	>200 GOhm x cm
Conductor stranding:	Fine wire according to VDE 0295 Class 5/ IEC 60228 Class 5
Minimum bending radius:	Occasional flexing: 15 x outer diameter Fixed installation: 4 x outer diameter
Nominal voltage:	U_0/U: 300/500 V
Test voltage:	2000 V
Protective conductor:	G = with GN-YE protective conductor X = without protective conductor
Temperature range:	-50 °C to +180 °C (adequate ventilation required)

PN 0486/01_03.10 ©2012 Lapp Group - Technical changes reserved
Photographs are not to scale and do not represent detailed images of the respective products.

Part number	Number of cores and mm² per conductor	Outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)
ÖLFLEX® HEAT 180 SiHF				
0046001	2 X 0,75	6,4	14.4	59
0046002	3 G 0,75	6,8	21.6	70
00460033	4 G 0,75	7,6	28.8	89
00460043	5 G 0,75	8,5	36.0	112
0046005	6 G 0,75	9,2	43.2	131
0046006	7 G 0,75	9,2	50.4	136
0046007	2 X 1	6,6	19.2	66
0046008	3 G 1	7.0	29.0	79
00460093	4 G 1	7,9	38.4	101
00460103	5 G 1	8,8	48.0	127
0046012	7 G 1	9,5	67.0	156
0046013	2 X 1,5	7,6	29.0	90
0046014	3 G 1,5	8.0	43.0	109
00460153	4 G 1,5	8,8	58.0	134
00460163	5 G 1,5	9,6	72.0	163
0046018	7 G 1,5	10,4	101.0	202
0046039	12 G 1,5	14.0	173.0	361
0046040	16 G 1,5	16,2	230.4	478
0046041	20 G 1,5	17,5	288.0	574
0046042	24 G 1,5	19,8	345.6	720
0046019	2 X 2,5	8,8	48.0	128
0046020	3 G 2,5	9,7	72.0	167
00460213	4 G 2,5	10,6	96.0	206
00460223	5 G 2,5	11,6	120.0	251
0046024	7 G 2,5	12,6	168.0	313
0046025	2 X 4	10,8	76.8	196
0046026	3 G 4	11,5	115.0	241
00460273	4 G 4	12,6	154.0	300
00460283	5 G 4	14.0	192.0	374

PN 0486/01_03.10

©2012 Lapp Group - Technical changes reserved

Photographs are not to scale and do not represent detailed images of the respective products.

Part number	Number of cores and mm² per conductor	Outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)
0046030	7 G 4	15,6	269.0	486
0046031	2 X 6	12,4	116.0	268
0046032	3 G 6	13,2	173.0	333
00460333	4 G 6	14,7	230.0	425
00460343	5 G 6	16,6	288.0	538
0046036	7 G 6	18,6	403.0	705
00460373	4 G 10	19,4	384.0	707
00460453	5 G 10	21,6	480.0	878
00460383	4 G 16	21,4	614.0	1004

PN 0486/01_03.10 ©2012 Lapp Group - Technical changes reserved
Photographs are not to scale and do not represent detailed images of the respective products.