Reducing plug - RPS - 0201647

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



Reducing plug, Color: gray

RoHS

Key Commercial Data

Packing unit	1 STK
Minimum order quantity	10 STK
GTIN	4 017918 099046
GTIN	4017918099046
Weight per Piece (excluding packing)	5.640 g
Custom tariff number	85366990
Country of origin	Poland

Technical data

Technical data

Color	gray
Material	silver-plated brass
Number of positions	1
Flammability rating according to UL 94	V2
Ambient temperature (operation)	-40 °C ... 100 °C

Standards and Regulations

Flammability rating according to UL 94	V2

Environmental Product Compliance

China RoHS	Environmentally Friendly Use Period = 50

Reducing plug - RPS - 0201647

Technical data

Environmental Product Compliance

	For details about hazardous substances go to tab “Downloads”, Category “Manufacturer's declaration”

Classifications

eCl@ss

eCl@ss 4.0	27141199
eCl@ss 4.1	27141199
eCl@ss 5.0	27141145
eCl@ss 5.1	27141145
eCl@ss 6.0	27141120
eCl@ss 7.0	27141120
eCl@ss 8.0	27440313
eCl@ss 9.0	27440313

ETIM

ETIM 2.0	EC000897
ETIM 3.0	EC000897
ETIM 4.0	EC002498
ETIM 5.0	EC002255

UNSPSC

UNSPSC 6.01	30211802
UNSPSC 7.0901	39121402
UNSPSC 11	39121402
UNSPSC 12.01	39121402
UNSPSC 13.2	39121402

Approvals

Approvals

Approvals

EAC

Ex Approvals

Reducing plug - RPS - 0201647

Approvals

Approval details

EAC	EAC-Zulassung

Phoenix Contact 2016 © - all rights reserved
http://www.phoenixcontact.com