LTC Batteries

SL-350 Size: ½AA

› Standard use and stand-by

Performance Data
(Typical values for batteries stored at +25 °C for one year)

System	Lithium Thionyl Chloride
Nominal voltage	3.6 V
Nominal capacity	1.2 Ah
Nominal current	0.6 mA
Max. continuous discharge current	6 mA
Anode surface area	6 cm^2
Lithium content	0.35 g
Weight	9.6 g
Volume	4 cm^3
Temperature range	–55 °C ... +85 °C



Typical Discharge Curves at +25 °C



Available Capacity



SL-350/S



SL-350/T



SL-350/P



Operating Voltage



SL-350/PR



SL-350/PT



Available Terminations		Catalogue No.
SL-350/S	Standard	11 1 03501 00
SL-350/T	Tags	11 1 03502 00
SL-350/P	Pins	11 1 03503 00
SL-350/PR	Pins radial	11 1 03506 00
SL-350/PT	Polarized tags	11 1 03508 00

WARNING: Fire, explosion, and severe burn hazard. Do not recharge, disassemble, heat above 100 °C, incinerate, or expose contents to water.

Any values given here are for informational purposes only. They also depend on actual conditions of use and are not warranties of future performance. Subject to change.

Tadiran Batteries GmbH • Industriestr. 22 • 63654 BÜDINGEN
GERMANY • Tel.: +49 (0)6042 954-0 • www.tadiranbatteries.de

PDC13Eng