DK 97 EB

Art. No. 50212 – 8 Ω







Einbau-Druckkammerhorn-Lautsprecher in wasserfester Ausführung mit 8 Ohm Impedanz. Hohe IP-Schutzklasse, hoher Schalldruck, gute Sprachverständlichkeit, kompakte Bauweise. Der Lautsprecher erfüllt alle wichtigen Normen aus dem Zugbereich, wie EN50155, EN45545 oder EN61373. Dazu gehören Temperatur-

Anwendungsmöglichkeiten:
– Beschallung von Werkhallen, Bahnhöfen usw.
– Außenbeschallung an Fahrzeugen
– Einsatz in Alarmanlagen
– Einbau von vorne und hinten möglich

Build in Horn Speaker *with waterproofed design and 8 Ohm impedance. High IP protection class, high sound pressure level, good voice reproduction, compact dimensions. The loudspeaker fulfils all important standards from the train sector, such as EN50155, EN45545 or EN61373. These include temperature and humidity standards, IP67, vibration and shock tests and fire tests.*

Typical applications:
– Public address in factories, railway stations etc.
– Outdoor PA for vehicles
– Use in alarm/alert systems
– Installation from front and rear side possible

Technische Daten / *Technical Data*

Nennbelastbarkeit *Rated power*	6 W
Impedanz *Impedance*	8 Ω
Mittlerer Schalldruckpegel *Mean sound pressure level*	93 dB (1 W/1 m)
Übertragungsbereich (–10 dB) *Frequency response (–10 dB)*	350–20.000 Hz
Resonanzfrequenz *Resonant frequency*	460 Hz
Anschluss *Terminal*	abisolierte Kabelenden stripped ends
Gewicht netto *Net weight*	335 g





