
Item no.:	750-323
Product description:	PROFIBUS DP FIELDBUS COUPLER 12 MBaud DIGITAL SIGNALS





Produkt kann von Bild abweichen / product may differ

Packing unit 1 piece

RoHS compliant

Product group	15 (I/O System)
Max. no. of nodes	96 with repeater
Max. no. Of I/O points	ca. 6000 (depends on Master)
Transmission medium	Cu-cable acc. to EN 50170
Max. length of fieldbus segment	100 m ... 1200 m (depends on the baud rate / on the cable)
Baud rate	9.6 kBaud ... 12 Mbaud
Transmission time	typ. 1 ms (10 Modules; 32 E, 32 A/Mod;at 12 Mbaud and digital Signals)max. 3.3 ms
Buscoupler connection	1 x D-SUB 9; socket
Conformity marking	CE
Max. no. of I/O modules	64
Configuration	via PC or PLC
Voltage supply	DC 24 V (-15% / + 20%)
Input current (max)	500 mA
Efficiency of the power supply	87 %
Internal current consumption	350 mA
Total current for the I/O modules	1600 mA
Isolation	500 V system / supply

Voltage via power jumper contacts (max)	DC 24 V (-15% / + 20%)
Current via power jumper contacts (max)	10
Operating temperature	0 °C ... + 55 °C
Storage temperature	-25 °C ... +85 °C
Relative air humidity	95 %

Vibration resistance	acc. IEC 60068-2-6
Shock resistance	acc. IEC 60068-2-27
Degree of protection	IP 20
EMC immunity to interference	acc. EN 50082-2 (96)
EMC emission of interference	acc. EN 50081-2 (94)
Cross section [mm²]	0.08 - 2.5 mm²
Cross section [AWG]	28 - 14 AWG
Connection method	CAGE CLAMP® CONNECTION
Weight	181 g
Color	light gray
Height	65 mm
Height	2.56 in
Width	51 mm
Width	2.008 in
Depth	100 mm
Depth	3.937 in
Strip length from	8 mm
Strip length to	9 mm
Strip length	0.33 in
Manuals	available as download on the Internet under
Mounting	TS 35

Item no.	Admission office	Approval no.	Voltage [V]	Current [A]	Cross section [mm²]
750-323	ABS	03-HG374860/3-PDA			
750-323	BSH	Bescheinigung Nr. 467			
750-323	BV	13453/C0 BV			
750-323	DNV	A-12306			
750-323	GL	26 898 - 05 HH			
750-323	IECEx	IECEx PTB 07.0064X			
750-323	KR	HMB05880-AC001			
750-323	LR	02/20026 (E2)			
750-323	NK	TA06190M			
750-323	PRS	TE/1720/880590/08			
750-323	Rina	ELE153207CS001			
750-323	UL	E175199 Sec.1			
750-323	UL	E198726 Sec.1			
750-323	UL DEMKO A/S	08 ATEX 142851 X			

Sorting criteria: admission office - approval number

© WAGO Kontakttechnik GmbH & Co. KG

Specifications are subject to changes and errors may be expected