

Product information

Erem

676E

Code No. : **T676E**

Side cutter - pointed relieved head
- This is the narrowest head shape.
- The underside is relieved and facilitates optimum access even to extremely hard-to-reach areas.
- Short, robust head

Technical Data

Cut:	Flush
Length:	110 mm / 4.331 Inch
Weight:	48 g / 1.69 oz.
Length of cutting edges:	9 mm / .354 Inch
Head width:	9 mm / .354 Inch
Head thickness:	6 mm / .236 Inch
Head length:	15 mm / .590 Inch
Max. cutting capability	
Hard wire:	-
Medium hardness:	Ø 0,6 mm / .023 Inch
Copper wire:	Ø 0,8 mm /.031 Inch

Series 600 Micro

- Miniature cutter
- Offers a wide variety of head shapes for access in difficult to reach areas
- Suitable for SMD and leads (670EP, 670EPF)
- Made from high grade tool steel with cutting edges hardened to 63-65 HRc
- Non-reflecting surface, ESD-safe, resharpenable

Erem Cutters and Tip Cutters

- Internal patented Erem Magic Spring
  - Reduce costs by long life
  - Constant spring force
  - Guarantees more than 1 million operations
- High precision screw joint
  - Smooth jaw action with no play
  - Smooth cutting operation with no jaw overlapping

- Induction-hardened cutting edges in Rockwell hardness 63 - 65 HRc
  for exceptionally long life
- EMOS maximum opening stop
  limits the cutting-edge tips from opening more than 5 mm / .197 Inch. The limited extent to which the handles can open prevent user hand fatigue.
- Ergonomically shaped handles
  for high comfort, better grip and added safety
- Erem cut:
  Options for semi flush, full flush or super flush cuts