SKT 24

THYRISTOR BRIDGE,SCR,BRIDGE



Stud Thyristor

Line Thyristor

SKT 24

Features

- Hermetic metal case with glass insulator
- Threaded stud ISO M6 or UNF 1/4-28
- International standard case

Typical Applications*

- DC motor control (e. g. for machine tools)
- Controlled rectifiers (e. g. for battery charging)
- AC controllers (e. g. for temperature control)
- Recommended snubber network e. g. for $V_{VRMS} \leq 400$ V: R = 100 Ω/5 W, C = 0,1 µF

1) Available with UNF thread 1/4-28 UNF2A, e. g. SKT 24/12E UNF

V_{RSM} V	V_{RRM}, V_{DRM} V	I_{TRMS} = 50 A (maximum value for continuous operation) I_{TAV} = 24 A (sin. 180; T_c = 95 °C)		
500	400	SKT 24/04D		
900	800	SKT 24/08D		
1300	1200	SKT 24/12E[1)]		
1500	1400	SKT 24/14E		
1700	1600	SKT 24/16E[1)]		
1900	1800	SKT 24/18E		

Symbol	Conditions	Values	Units
I_{TAV}	sin. 180; T_c = 100 (85) °C;	22 (29)	A
I_D	K5; T_a = 45 °C; B2 / B6	22 / 30	A
	K3; T_a = 45 °C; B2 / B6	28 /40	A
I_{RMS}	K5; T_a = 45 °C; W1C	24	A
I_{TSM}	T_{vj} = 25 °C; 10 ms	450	A
	T_{vj} = 130 °C; 10 ms	380	A
i²t	T_{vj} = 25 °C; 8,35 ... 10 ms	1000	A²s
	T_{vj} = 130 °C; 8,35 ... 10 ms	720	A²s
V_T	T_{vj} = 25 °C; I_T = 75 A	max. 1,9	V
$V_{T(TO)}$	T_{vj} = 130 °C	max. 1	V
r_T	T_{vj} = 130 °C	max. 10	mΩ
I_{DD}; I_{RD}	T_{vj} = 130 °C; V_{RD} = V_{RRM}; V_{DD} = V_{DRM}	max. 8	mA
t_{gd}	T_{vj} = 25 °C; I_G = 1 A; di_G/dt = 1 A/µs	1	µs
t_{gr}	V_D = 0,67 * V_{DRM}	2	µs
$(di/dt)_{cr}$	T_{vj} = 130 °C	max. 50	A/µs
$(dv/dt)_{cr}$	T_{vj} = 130 °C ; SKT ...D / SKT ...E	max. 500 / 1000	V/µs
t_q	T_{vj} = 130 °C ,	80	µs
I_H	T_{vj} = 25 °C; typ. / max.	80 / 150	mA
I_L	T_{vj} = 25 °C; typ. / max.	150 / 300	mA
V_{GT}	T_{vj} = 25 °C; d.c.	min. 3	V
I_{GT}	T_{vj} = 25 °C; d.c.	min. 100	mA
V_{GD}	T_{vj} = 130 °C; d.c.	max. 0,25	V
I_{GD}	T_{vj} = 130 °C; d.c.	max. 3	mA
$R_{th(j-c)}$	cont.	0,8	K/W
$R_{th(j-c)}$	sin. 180	0,9	K/W
$R_{th(j-c)}$	rec. 120	0,95	K/W
$R_{th(c-s)}$		0,5	K/W
T_{vj}		- 40 ... + 130	°C
T_{stg}		- 40 ... + 150	°C
V_{isol}		-	V~
M_s	to heatsink	2,5	Nm
a		5 * 9,81	m/s²
m	approx.	13	g
Case		B 2	



SKT

 © by SEMIKRON



Fig. 1L Power dissipation vs. on-state current



Fig. 1R Power dissipation vs. ambient temperature



Fig. 2 Rated on-state current vs. case temperature



Fig. 3 Recovered charge vs. current decrease



Fig. 4 Transient thermal impedance vs. time



Fig. 5 Thermal resistance vs. conduction angle

 © by SEMIKRON



Fig. 6 On-state characteristics



Fig. 7 Power dissipation vs. on-state current



Fig. 8 Surge overload curent vs. time

 © by SEMIKRON



Fig. 9 Gate trigger characteristics



Case B 2 (IEC 60191-2: A11M, A11U; JEDEC: TO-208AA (TO-48))

* The specifications of our components may not be considered as an assurance of component characteristics. Components have to be tested for the respective application. Adjustments may be necessary. The use of SEMIKRON

 © by SEMIKRON

products in life support appliances and systems is subject to prior specification and written approval by SEMIKRON. We therefore strongly recommend prior consultation of our personal.

 © by SEMIKRON