
ISO8200B

Galvanic isolated octal high-side smart power solid state relay

Datasheet - production data



PowerSO-36

Features

Type	V_{demag} (1)	$R_{DS(on)}$ (1)	I_{OUT} (1)	V_{cc}
ISO8200B	V_{cc} - 45 V	0.11 Ω	0.7 A	45 V

1. Per channel

- Parallel input interface
- Direct and synchronous control mode
- High common mode transient immunity
- Output current: 0.7 A per channel
- Short-circuit protection
- Channel overtemperature protection
- Thermal independence of separate channels
- Common output disable pin
- Case overtemperature protection
- Loss of GND_{cc} and V_{cc} protection
- Undervoltage shutdown with auto restart and hysteresis
- Overvoltage protection (V_{cc} clamping)
- Very low supply current
- Common fault open drain output
- 5 V and 3.3 V TTL/CMOS compatible I/Os
- Fast demagnetization of inductive loads
- Reset function for IC outputs disable
- ESD protection
- IEC 61000-4-2, IEC 61000-4-4, IEC 61000-4-5 and IEC 61000-4-8 compliant

Applications

- Programmable logic control
- Industrial PC peripheral input/output
- Numerical control machines
- Drivers for all types of loads (resistive, capacitive, inductive)

Description

The ISO8200B is a galvanic isolated 8-channel driver featuring a very low supply current. It contains 2 independent galvanic isolated voltage domains (V_{cc} for the Power stage and V_{dd} for the Digital stage). Additional embedded functions are: loss of GND protection, undervoltage shutdown with hysteresis, and reset function for immediate power output shutdown.

The IC is intended to drive any kind of load with one side connected to ground. Active channel current limitation combined with thermal shutdown, (independent for each channel), and automatic restart, protect the device against overload and short-circuit. In overload conditions, if junction temperature overtakes threshold, the channel involved is turned off and on again automatically after the IC temperature decreases below a reset threshold. If this condition causes case temperature to reach limit threshold TCR, the overloaded channel is turned off and it only restarts when case and junction temperature decrease down to the reset thresholds. Non-overloaded channels continue operating normally. An internal circuit provides an OR-wired not latched common FAULT indicator signaling the channel OVT. The FAULT pin is an open drain active low fault indication pin.

This is information on a product in full production. www.st.com

Contents

1 Block diagram 6

2 Pin connection 7

3 Absolute maximum ratings 9

4 Thermal data 10

5 Electrical characteristics 10

6 Functional description 16

6.1 Parallel interface 16

6.1.1 Input signals (IN1 to IN8) 16

6.1.2 Load input data ($\overline{\text{LOAD}}$) 16

6.1.3 Output synchronization ($\overline{\text{SYNC}}$) 16

6.1.4 Watchdog 17

6.1.5 Output enable (OUT_EN) 17

6.2 Direct control mode (DCM) 18

6.3 Synchronous control mode (SCM) 19

6.4 Fault indication 22

6.4.1 Junction overtemperature and case overtemperature 22

7 Power section 24

7.1 Current limitation 24

7.2 Thermal protection 25

8 Reverse polarity protection 27

9 Reverse polarity on V_{dd} 28

10 Demagnetization energy 29

11 Conventions 30

11.1 Supply voltage and power output conventions 30

12 Thermal information 30
12.1 Thermal impedance 30
13 Package mechanical data 31
14 Ordering information 34
15 Revision history 35

List of tables


Table 1. Pin description . . . 7
Table 2. Absolute maximum ratings . . . 9
Table 3. Thermal data . . . 10
Table 4. Power section . . . 10
Table 5. Digital supply voltage . . . 11
Table 6. Diagnostic pin and output protection function . . . 11
Table 7. Power switching characteristics (V_{CC} = 24 V; -40 °C < T_J < 125 °C) . . . 12
Table 8. Logic input and output . . . 13
Table 9. Parallel interface timings (V_{dd} = 5 V; V_{cc}= 24 V; -40 °C < T_J < 125 °C) . . . 14
Table 10. IEC 60747-5-2 insulation characteristics . . . 15
Table 11. Interface signal operation (general) . . . 16
Table 12. Interface signal operation in direct control mode . . . 18
Table 13. Interface signal operation in synchronous control mode . . . 20
Table 14. PowerSO-36 mechanical data . . . 32
Table 15. Footprint data . . . 33
Table 16. Ordering information . . . 34
Table 17. Document revision history . . . 35

List of figures

Figure 1. Block diagram . . . 6
Figure 2. Pin connection (top view) . . . 7
Figure 3. $R_{DS(on)}$ measurement . . . 12
Figure 4. dV/dT . . . 13
Figure 5. td(ON)-td(OFF) synchronous mode . . . 13
Figure 6. td(ON)-td(OFF) direct control mode . . . 13
Figure 7. Watchdog behavior . . . 17
Figure 8. Output channel enable timing . . . 17
Figure 9. Direct control mode IC configuration . . . 18
Figure 10. Direct control mode time diagram . . . 19
Figure 11. Synchronous control mode IC configuration . . . 20
Figure 12. Synchronous control mode time diagram . . . 21
Figure 13. Multiple device synchronous control mode . . . 21
Figure 14. Thermal status update (DCM) . . . 22
Figure 15. Thermal status update (SCM) . . . 23
Figure 16. Current limitation with different load conditions . . . 24
Figure 17. Thermal protection flowchart . . . 25
Figure 18. Thermal protection . . . 26
Figure 19. Reverse polarity protection . . . 27
Figure 20. Reverse polarity protection on V_{dd} . . . 28
Figure 21. Maximum demagnetization energy vs. load current typical values . . . 29
Figure 22. Supply voltage and power output conventions . . . 30
Figure 23. Simplified thermal model . . . 30
Figure 24. PowerSO-36 mechanical drawings . . . 31
Figure 25. Footprint recommended data . . . 33

1 Block diagram

Figure 1. Block diagram



2 Pin connection

Figure 2. Pin connection (top view)




Table 1. Pin description

Pin	Name	Description
1	NC	Not connected
2	V_{dd}	Positive logic supply
3	OUT_EN	Output enable
4	$\overline{SYNC}$	Chip select
5	$\overline{LOAD}$	Load input data
6	IN1	Channel 1 input
7	IN2	Channel 2 input
8	IN3	Channel 3 input
9	IN4	Channel 4 input
10	IN5	Channel 5 input
11	IN6	Channel 6 input
12	IN7	Channel 7 input
13	IN8	Channel 8 input
14	$\overline{FAULT}$	Common fault indication - active low
15	GNDdd	Input logic ground, negative logic supply
16	NC	Not connected

Table 1. Pin description (continued)

Pin	Name	Description
17	NC	Not connected
18	NC	Not connected
19	GNDcc	Output power ground
20	NC	Not connected
21	OUT8	Channel 8 power output
22	OUT8	Channel 8 power output
23	OUT7	Channel 7 power output
24	OUT7	Channel 7 power output
25	OUT6	Channel 6 power output
26	OUT6	Channel 6 power output
27	OUT5	Channel 5 power output
28	OUT5	Channel 5 power output
29	OUT4	Channel 4 power output
30	OUT4	Channel 4 power output
31	OUT3	Channel 3 power output
32	OUT3	Channel 3 power output
33	OUT2	Channel 2 power output
34	OUT2	Channel 2 power output
35	OUT1	Channel 1 power output
36	OUT1	Channel 1 power output
TAB	TAB	Exposed tab internally connected to Vcc, positive power supply voltage

3 Absolute maximum ratings

Table 2. Absolute maximum ratings

Symbol	Parameter	Min.	Max.	Unit
V_{CC}	Power supply voltage	-0.3	45	V
V_{dd}	Digital supply voltage	-0.3	6.5	V
V_{IN}	DC input pins, I_d and output enable voltage	-0.3	+6.5	V
V_{FAULT}	Fault voltage	-0.3	+6.5	V
I_{GNDdd}	DC digital ground reverse current		-25	mA
I_{OUT}	Channel output current (continuous)		Internally limited	A
I_{GNDcc}	DC power ground reverse current		-250	mA
I_R	Reverse output current (per channel)		-5	A
I_{IN}	DC input pins, I_d and output enable current	-10	+ 10	mA
I_{FAULT}	Fault current	-10	+ 10	mA
V_{ESD}	Electrostatic discharge with human body model (R = 1.5 KΩ; C = 100 pF)		2000	V
EAS	Single pulse avalanche energy per channel not simultaneously		3	J
PTOT	Power dissipation at T_c = 25 °C		Internally limited(1)	W
T_J	Junction operating temperature		Internally limited(1)	°C
T_{STG}	Storage temperature		-55 to 150	°C

1. Protection functions are intended to avoid IC damage in fault conditions and are not intended for continuous operation. Continuous or repetitive operations of protection functions may reduce the IC lifetime.

4 Thermal data

Table 3. Thermal data

Symbol	Parameter	Max. value	Unit
$R_{thj\text{-}case}$	Thermal resistance, junction-case(1)	1.3	°C/W
$R_{thj\text{-}amb}$	Thermal resistance, junction-ambient(2)	15	°C/W

1. For each channel.
2. PSSO36 mounted on the product evaluation board STEVAL-IFP015V2 (FR4, 4 layers, 8 cm^2 for each layer, copper thickness 35 µm.

5 Electrical characteristics

(10.5 V < V_{CC} < 36 V; -40 °C < T_J < 125 °C, unless otherwise specified).

Table 4. Power section

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
$V_{cc(under)THON}$	V_{cc} undervoltage turn-ON threshold			9.5	10.5	V
$V_{cc(under)THOFF}$	V_{cc} undervoltage turn-OFF threshold			9		V
$V_{cc(hys)}$	V_{cc} undervoltage hysteresis		0.35	0.5		V
$V_{ccclamp}$	Clamp on V_{cc} pin	I_{clamp} = 20 mA	45	50	52	V
$R_{DS(on)}$	On-state resistance (1)	I_{OUT} = 0.5 A, T_J = 25 °C I_{OUT} = 0.5 A T_J = 125 °C		0.12	 0.24	Ω Ω
R_{pd}	Output pull-down resistor			210		kΩ
I_{cc}	Power supply current	All channels in OFF state All channels in ON state		5 9		mA mA
I_{LGND}	Ground disconnection output current	V_{cc}= V_{GND} =0 V V_{OUT}= -24 V			500	µA
V_{OUT}(OFF)	Off-state output voltage	Channel OFF and I_{OUT} = 0 A			1	V
I_{OUT}(OFF)	Off-state output current	Channel OFF and V_{OUT} = 0 V			5	µA

1. See *Figure 3.*

Table 5. Digital supply voltage

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
$V_{dd(under)}$	V_{dd} undervoltage protection turn-OFF threshold		2.8	2.9	3	V
$V_{dd(hys)}$	V_{dd} undervoltage hysteresis			0.1		V
I_{dd}	I_{dd} supply current	V_{dd} = 5 V and input channel with a steady logic level		4.5	6	mA
		V_{dd} = 3.3 V and input channel with a steady logic level		4.4	5.9	mA

Table 6. Diagnostic pin and output protection function

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
V_{FAULT}	$\overline{FAULT}$ pin open drain voltage output low	I_{FAULT} = 10 mA			0.4	V
I_{LFAULT}	$\overline{FAULT}$ output leakage current	V_{FAULT} = 5 V			1	µA
I_{PEAK}	Maximum DC output current (1)			1.4		A
I_{LIM}	Short-circuit current limitation	R_{LOAD} = 0 Ω	0.7	1.1	1.7	A
H_{yst}	I_{LIM} tracking limits	R_{LOAD} = 0 Ω		0.3		A
T_{JSD}	Junction shutdown temperature		150	170		°C
T_{JR}	Junction reset temperature			150		°C
T_{HIST}	Junction thermal hysteresis			20		°C
T_{CSD}	Case shutdown temperature		115	130	145	°C
T_{CR}	Case reset temperature			110		°C
T_{CHYST}	Case thermal hysteresis			20		°C
V_{demag}	Output voltage at turn-OFF	I_{OUT} = 0.5 A; I_{LOAD} > = 1 mH	V_{cc}-45	V_{cc}-50	V_{cc}-52	V

1. Current level from open load to short-circuit until thermal intervention.

Table 7. Power switching characteristics (V_{CC} = 24 V; -40 °C < T_J < 125 °C)

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
dV/dt(ON)	Turn-ON voltage slope	I_{OUT} = 0.5 A, resistive load 48 Ω	-	5.6	-	V/µs
dV/dt(OFF)	Turn-OFF voltage slope	I_{OUT} = 0.5 A, resistive load 48 Ω	-	2.81	-	V/µs
t_d(ON)	Turn-ON delay time(1)	I_{OUT} = 0.5 A, resistive load 48 Ω	-	17	22	µs
t_d(OFF)	Turn-OFF delay time (1)	I_{OUT} = 0.5 A, resistive load 48 Ω	-	22	40	µs
t_f	Fall time (1)	I_{OUT} = 0.5 A, resistive load 48 Ω	-	5	-	µs
t_r	Rise time (1)	I_{OUT} = 0.5 A, resistive load 48 Ω	-	5	-	µs

1. See *Figure 4*, *Figure 5*, and *Figure 6*.

Figure 3. $R_{DS(on)}$ measurement




Figure 4. dV/dT




Figure 5. td(ON)-td(OFF) synchronous mode




Figure 6. td(ON)-td(OFF) direct control mode




Table 8. Logic input and output

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
V_{IL}	Logic input, $\overline{LOAD}$ and OUT_EN low level voltage		-0.3		0.3 x V_{dd}	V
V_{IH}	Logic input, $\overline{LOAD}$ and OUT_EN high level voltage		0.7 x V_{dd}		V_{dd}+0.3	V
$V_{I(HYST)}$	Logic input, $\overline{LOAD}$ and OUT_EN hysteresis voltage	V_{dd} = 5 V		100		mV
I_{IN}	Logic input, $\overline{LOAD}$ and OUT_EN current	V_{IN} = 5 V	10			µA
t_{WM}	Power side watchdog time		272	320	400	µs

Table 9. Parallel interface timings (V_{dd} = 5 V; V_{cc}= 24 V; -40 °C < T_J < 125 °C)

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
$t_{dis(SYNC)}$	$\overline{SYNC}$ disable time	Sync. control mode	10			µs
$t_{dis(DCM)}$	$\overline{SYNC\ LOAD}$ disable time	Direct control mode	80			ns
$t_{w(SYNC)}$	$\overline{SYNC}$ negative pulse width	Sync. control mode	20		195	µs
$t_{su(LOAD)}$	$\overline{LOAD}$ setup time	Sync. control mode	80			ns
$t_{h(LOAD)}$	$\overline{LOAD}$ hold time	Sync. control mode	400			ns
$t_{w(LOAD)}$	$\overline{LOAD}$ pulse width	Sync. control mode	240			ns
$t_{su(IN)}$	Input setup time		80			ns
$t_{h(IN)}$	Input hold time		10			ns
$t_{w(IN)}$	Input pulse width	Sync. control mode	160			ns
		Direct control mode	20			µs
t_{INLD}	IN to $\overline{LOAD}$ time	Direct control mode From IN variation to $\overline{LOAD}$ falling edge	80			ns
t_{LDIN}	$\overline{LOAD}$ to IN time	Direct control mode From $\overline{LOAD}$ falling edge to IN variation	400			ns
$t_{w(OUT_EN)}$	OUT_EN pulse width		150			ns
$t_{p(OUT_EN)}$	OUT_EN propagation delay			22	40	µs
$t_{jitter(SCM)}$	Jitter on single channel	Sync. mode			6	µs
$t_{jitter(DCM)}$		Direct mode			20	
$f_{refresh}$	Refresh delay			15		kHz

Table 10. IEC 60747-5-2 insulation characteristics

Symbol	Parameter	Test conditions	Value	Unit
CTI	Comparative tracking index (tracking resistance)	DIN IEC 112/VDE 0303 part 1	≥ 400	V
	Isolation group	Material group (DIN VDE 0110, 1/89, table 1	II	
V_{ISO}	Isolation voltage per UL 1577	100% production V_{TEST} = 1.2 x V_{ISO}=1644 V, t = 1 s	1370	V_{PEAK}
V_{PR}	Input-to-output test voltage as per IEC 60747-5-2	100% production test method b, t_m = 1 s partial discharge < 5 pC	1644	V_{PEAK}
		Characterization test method a, t_m = 10 s partial discharge < 5 pC	1315	V_{PEAK}
V_{IOTM}	Transient overvoltage as per IEC 60747-5-2	Characterization test V_{TEST} = 1.2 x V_{IOTM}, t = 60 s	3500	V_{PEAK}
CLR	Clearance (minimum external air gap)	Measured from input terminals to output terminals, the shortest distance through air	2.6	mm
CPG	Creepage (minimum external tracking)	Measured from input terminals to output terminals, the shortest distance path analog body	2.6	mm

6 Functional description

6.1 Parallel interface

Smart parallel interface built-in ISO8200B offers three interfacing signals easily managed by a microcontroller.

The $\overline{\text{LOAD}}$ signal enables the input buffer storing the value of the channel inputs.

The $\overline{\text{SYNC}}$ signal copies the input buffer value into the transmission buffer and manages the synchronization between low voltage side and the channel outputs on the isolated side.

The OUT_EN signal enables the channel outputs.

An internal refresh signal updates the configuration of the channel outputs with a $f_{refresh}$ frequency. This signal can be disabled forcing low the $\overline{\text{SYNC}}$ input when $\overline{\text{LOAD}}$ is high.

$\overline{\text{SYNC}}$ and $\overline{\text{LOAD}}$ pins can be in direct control mode (DCM) or synchronous control mode (SCM).

The operation of these two signals is described as follows:

Table 11. Interface signal operation (general)

$\overline{\text{LOAD}}$	$\overline{\text{SYNC}}$	OUT_EN	Device behavior
Don't care	Don't care	Low(1)	The outputs are disabled (turned off)
High	High	High	The outputs are left unchanged
Low	High	High	The input buffer is enabled The outputs are left unchanged
High	Low	High	The internal refresh signal is disabled The transmission buffer is updated The outputs are left unchanged
Low	Low	High	The device operates in direct control mode as described in the respective paragraph

1. The outputs are turned off on OUT_EN falling edge and they are kept disabled as long as it is low.

6.1.1 Input signals (IN1 to IN8)

Inputs from IN1 to IN8 are the driving signals of the corresponding OUT1 to OUT8 outputs. Data are direct loaded on related outputs if $\overline{\text{SYNC}}$ and $\overline{\text{LOAD}}$ inputs are low (DCM operation) or stored into input buffer when $\overline{\text{LOAD}}$ is low and SYNC is high.

6.1.2 Load input data ($\overline{\text{LOAD}}$)

The input is active low; it stores the data from IN1 to IN8 into the input buffer.

6.1.3 Output synchronization ($\overline{\text{SYNC}}$)

The input is active low; it enables the ISO8200B transmission buffer loading input buffer data and manages the transmission between the two isolated sides of the device.


6.1.4 Watchdog

The isolated side of the device provides a watchdog function in order to guarantee a safe condition when V_{dd} supply voltage is missing.

If the logic side does not update the output status within t_{WD}, all outputs are disabled until a new update request is received.

The refresh signal is also considered a valid update signal, so the isolated side watchdog does not protect the system from a failure of the host controller (MCU freezing).


Figure 7. Watchdog behavior



6.1.5 Output enable (OUT_EN)

This pin provides a fast way to disable all outputs simultaneously. When the OUT_EN pin is driven low the outputs are disabled. To enable the output stage, the OUT_EN pin has to be raised. This timing execution is compatible with an external reset push, safety requirement, and allows, in a PLC system, the microcontroller polling to obtain all internal information during a reset procedure.

Figure 8. Output channel enable timing



6.2 Direct control mode (DCM)

When $\overline{\text{SYNC}}$ and $\overline{\text{LOAD}}$ inputs are driven by the same signal, the device operates in direct control mode (DCM).

In DCM the $\overline{\text{SYNC}}$ / $\overline{\text{LOAD}}$ signal operates as an active low input enable:

- when the signal is high, the current output configuration is kept regardless the input values
- when the signal is low, each channel input directly drives the respective output

This operation mode can also be set shorting both signals to the digital ground; in this case the channel outputs are always directly driven by the inputs except when OUT_EN is low (outputs disabled).

Table 12. Interface signal operation in direct control mode

$\overline{\text{SYNC}}$ / $\overline{\text{LOAD}}$	OUT_EN	Device behavior
Don't care	Low(1)	The outputs are disabled (turned off)
High	High	The outputs are left unchanged
Low	High	The channel inputs drive the outputs

1. The outputs are turned off on OUT_EN falling edge and they are kept disabled as long as it is low.

Figure 9. Direct control mode IC configuration





Figure 10. Direct control mode time diagram



6.3 Synchronous control mode (SCM)

When $\overline{\text{SYNC}}$ and $\overline{\text{LOAD}}$ inputs are independently driven, the device can operate in synchronous control mode (SCM). The SCM is used to reduce the jittering of the outputs and to drive all outputs of different devices at the same time.

In SCM the $\overline{\text{LOAD}}$ signal is forced low to update the input buffer while the $\overline{\text{SYNC}}$ signal is high. The $\overline{\text{LOAD}}$ signal is raised and the $\overline{\text{SYNC}}$ one is forced low for at least $t_{SYNC(SCM)}$. During this period, the internal refresh is disabled and any pending transmission between the low voltage and the isolated side is completed. When the $\overline{\text{SYNC}}$ signal is raised the channel output configuration is changed according to the one stored in the input.

If the $t_{SYNC(SCM)}$ limit is met, the maximum jitter of the channel outputs is t_{jitter}(SCM).

If more devices share the same SYNC signal, all device outputs change simultaneously with a maximum jitter related to maximum delay and maximum jitter for single device.

Table 13. Interface signal operation in synchronous control mode

$\overline{\text{LOAD}}$	$\overline{\text{SYNC}}$	OUT_EN	Device behavior
Don't care	Don't care	Low (1)	The outputs are disabled (turned off)
High	High	High	The outputs are left unchanged
Low	High	High	The input buffer is enabled The outputs are left unchanged
High	Low	High	The internal refresh signal is disabled The transmission buffer is updated The outputs are left unchanged
High	Rising edge	High	The outputs are updated according to the current transmission buffer value
Low	Low	High	Should be avoided (DCM operation only)

1. The outputs are turned off on OUT_EN falling edge and they are kept disabled as long as it is low.

Figure 11. Synchronous control mode IC configuration




Figure 12. Synchronous control mode time diagram





Figure 13. Multiple device synchronous control mode



6.4 Fault indication

The $\overline{\text{FAULT}}$ pin is an active low open drain output indicating fault conditions. This pin is active when at least one of the following conditions occurs:

- Junction overtemperature of one or more channels ($T_J > T_{TJSD}$)
- Communication error

6.4.1 Junction overtemperature and case overtemperature

The thermal status of the device is updated during each transmission sequence between the two isolated sides.

In SCM operation, when the $\overline{\text{LOAD}}$ signal is high and the $\overline{\text{SYNC}}$ one is low, the communication is disabled. In this case the thermal status of the device cannot be updated and the $\overline{\text{FAULT}}$ indication can be different from the current status.

In any case, the thermal protection of the channel outputs is always operative.

Figure 14. Thermal status update (DCM)





Figure 15. Thermal status update (SCM)



7 Power section


7.1 Current limitation

The current limitation process is active when the current sense connected on the output stage measures a current value, which is higher than a fixed threshold.

When this condition is verified the gate voltage is modulated to avoid the increase of the output current over the limitation value.

Figure 16 shows typical output current waveforms with different load conditions.

Figure 16. Current limitation with different load conditions



7.2 Thermal protection

The device is protected against overheating in case of overload conditions. During the driving period, if the output is overloaded, the device suffers two different thermal stresses, the former related to the junction, and the latter related to the case.

The two faults have different trigger thresholds: the junction protection threshold is higher than the case protection one; generally the first protection, that is active in thermal stress conditions, is the junction thermal shutdown. The output is turned off when the temperature is higher than the related threshold and turned back on when it goes below the reset threshold. This behavior continues until the fault on the output is present.

If the thermal protection is active and the temperature of the package increases over the fixed case protection threshold, the case protection is activated and the output is switched off and back on when the junction temperature of each channel in fault and case temperature is below the respective reset thresholds.

Figure 17 shows the thermal protection behavior, while *Figure 18* reports typical temperature trends and output vs. input state.

Figure 17. Thermal protection flowchart





Figure 18. Thermal protection



8 Reverse polarity protection

Reverse polarity protection can be implemented on board using two different solutions:

1. Placing a resistor (R_{GND}) between IC GND pin and load GND
2. Placing a diode between IC GND pin and load GND

If option 1 is selected, the minimum resistance value has to be selected according to the following equation:

Equation 1

$R_{GND} \geq V_{CC}/I_{GNDcc}$

where I_{GNDcc} is the DC reverse ground pin current and can be found in *Section 3: Absolute maximum ratings* of this datasheet.

Power dissipated by R_{GND} during reverse polarity situations is:

Equation 2

$P_D = (V_{CC})^2/R_{GND}$


If option 2 is selected, the diode has to be chosen by taking into account VRRM >$|V_{cc}|$ and its power dissipation capability:

Equation 3

$P_D \geq I_S * V_F$

Note: In normal conditions (no reverse polarity) due to the diode, there is a voltage drop between GND of the device and GND of the system.

Figure 19. Reverse polarity protection



This schematic can be used with any type of load.

9 Reverse polarity on V_{dd}

The reverse polarity on V_{dd} can be implemented on board by placing a diode between GND_{dd} pin and GND digital ground.


The diode has to be chosen by taking into account VRRM >$|V_{dd}|$ and its power dissipation capability:

Equation 4

$$P_D \geq I_{dd}*V_F$$


Note: In normal conditions (no reverse polarity), due to the diode, there is a voltage drop between GND_{dd} of the device and digital ground of the system.

Figure 20. Reverse polarity protection on V_{dd}



10 Demagnetization energy

Figure 21. Maximum demagnetization energy vs. load current typical values




11 Conventions

11.1 Supply voltage and power output conventions

Figure 22 shows the convention used in this paper for voltage and current usage.


Figure 22. Supply voltage and power output conventions



12 Thermal information

12.1 Thermal impedance

Figure 23. Simplified thermal model



13 Package mechanical data

In order to meet environmental requirements, ST offers these devices in different grades of ECOPACK® packages, depending on their level of environmental compliance. ECOPACK specifications, grade definitions and product status are available at: *www.st.com*. ECOPACK is an ST trademark.

Figure 24. PowerSO-36 mechanical drawings




Table 14. PowerSO-36 mechanical data

Dim.	mm		
	Min.	Typ.	Max.
A			3.60
a1	0.10		0.30
a2			3.30
a3	0		0.10
b	0.22		0.38
c	0.23		0.32
D(1)	9.40		9.80
E	13.90		14.50
E1(1)	10.90		11.10
E2			2.90
E3	5.8		6.2
e		0.65	
e3		11.05	
G	0		0.10
H	15.50		15.90
h			1.10
L	0.80		1.10
N			10°
S	0°		8°

Figure 25. Footprint recommended data




Table 15. Footprint data

Dim.	mm
A	9.5
B	14.7-15.0
C	12.5-12.7
D	6.3
E	0.46
G	0.65

14 Ordering information

Table 16. Ordering information

Order code	Package	Packaging
ISO8200B	PowerSO-36	Tube
ISO8200BTR	PowerSO-36	Tape and reel

15 Revision history

Table 17. Document revision history

Date	Revision	Changes
19-Oct-2012	1	Initial release.
01-Jul-2013	2	Updated *Figure 25: Footprint recommended data* and *Table 15: Footprint data*.
28-Oct-2013	3	Document status promoted from preliminary to production data. Added IEC bullet to features. Updated *Table 4*, *Table 6*, *Table 7*, and *Table 9*. Deleted table titled: “Insulation and safety-related specifications” and table titled: “Device immunity specifications”. Changed *Table 10: IEC 60747-5-2 insulation characteristics* Changed *Figure 10*.
12-Nov-2013	4	Added to *Table 10* CLR and CPG parameters.
29-Nov-2013	5	Removed V_{IORM} parameter from *Table 10*. Updated *Section 8: Reverse polarity protection*. Added *Section 9: Reverse polarity on V_{dd}* and *Section 10: Demagnetization energy*. Changed *Figure 19*. Added *Figure 20* and *Figure 21*.
24-Jan-2014	6	Changed *Figure 7*. Added note to *Table 3*. Added test conditions: T_J = 125 °C to *Table 4*. Added typ. and max. values of I_{dd} to *Table 5*. Added max. values of t_d(ON) and t_d(OFF) to *Table 7*. Added typ. and max. values of $t_{p(OUT_EN)}$ to *Table 9*. Added $t_{jitter(DCM)}$ value to *Table 9*.
03-Feb-2014	7	Updated *Figure 12*.
06-Feb-2014	8	Updated *Figure 12* and *Table 9*.

Please Read Carefully:

Information in this document is provided solely in connection with ST products. STMicroelectronics NV and its subsidiaries (“ST”) reserve the right to make changes, corrections, modifications or improvements, to this document, and the products and services described herein at any time, without notice.

All ST products are sold pursuant to ST’s terms and conditions of sale.

Purchasers are solely responsible for the choice, selection and use of the ST products and services described herein, and ST assumes no liability whatsoever relating to the choice, selection or use of the ST products and services described herein.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted under this document. If any part of this document refers to any third party products or services it shall not be deemed a license grant by ST for the use of such third party products or services, or any intellectual property contained therein or considered as a warranty covering the use in any manner whatsoever of such third party products or services or any intellectual property contained therein.

UNLESS OTHERWISE SET FORTH IN ST’S TERMS AND CONDITIONS OF SALE ST DISCLAIMS ANY EXPRESS OR IMPLIED WARRANTY WITH RESPECT TO THE USE AND/OR SALE OF ST PRODUCTS INCLUDING WITHOUT LIMITATION IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE (AND THEIR EQUIVALENTS UNDER THE LAWS OF ANY JURISDICTION), OR INFRINGEMENT OF ANY PATENT, COPYRIGHT OR OTHER INTELLECTUAL PROPERTY RIGHT.

ST PRODUCTS ARE NOT DESIGNED OR AUTHORIZED FOR USE IN: (A) SAFETY CRITICAL APPLICATIONS SUCH AS LIFE SUPPORTING, ACTIVE IMPLANTED DEVICES OR SYSTEMS WITH PRODUCT FUNCTIONAL SAFETY REQUIREMENTS; (B) AERONAUTIC APPLICATIONS; (C) AUTOMOTIVE APPLICATIONS OR ENVIRONMENTS, AND/OR (D) AEROSPACE APPLICATIONS OR ENVIRONMENTS. WHERE ST PRODUCTS ARE NOT DESIGNED FOR SUCH USE, THE PURCHASER SHALL USE PRODUCTS AT PURCHASER’S SOLE RISK, EVEN IF ST HAS BEEN INFORMED IN WRITING OF SUCH USAGE, UNLESS A PRODUCT IS EXPRESSLY DESIGNATED BY ST AS BEING INTENDED FOR “AUTOMOTIVE, AUTOMOTIVE SAFETY OR MEDICAL” INDUSTRY DOMAINS ACCORDING TO ST PRODUCT DESIGN SPECIFICATIONS. PRODUCTS FORMALLY ESCC, QML OR JAN QUALIFIED ARE DEEMED SUITABLE FOR USE IN AEROSPACE BY THE CORRESPONDING GOVERNMENTAL AGENCY.

Resale of ST products with provisions different from the statements and/or technical features set forth in this document shall immediately void any warranty granted by ST for the ST product or service described herein and shall not create or extend in any manner whatsoever, any liability of ST.

ST and the ST logo are trademarks or registered trademarks of ST in various countries.
Information in this document supersedes and replaces all information previously supplied.
The ST logo is a registered trademark of STMicroelectronics. All other names are the property of their respective owners.

© 2014 STMicroelectronics - All rights reserved

STMicroelectronics group of companies

Australia - Belgium - Brazil - Canada - China - Czech Republic - Finland - France - Germany - Hong Kong - India - Israel - Italy - Japan - Malaysia - Malta - Morocco - Philippines - Singapore - Spain - Sweden - Switzerland - United Kingdom - United States of America

www.st.com